



43 111/



B

P

1

43 111

□3

1

43 113

43 113

3

1



. / 5 5-

3

B



ASTM D1559   ASTM D5581   AASHTO T245   ASTM D6926



	<b>76-B4442</b> <b>76-B4443</b> <b>76-B4444</b>	<b>76-B4462</b> <b>76-B4463</b> <b>76-B4464</b>
	5-- T	/ --- T
,	22 2	22 2
	65 2	.161
	1 203 6d	. - / . - - . hd
	1 24 0	1 24 /
	052 14- .534	1/0 245 .53.
	. 2- hd	. 4- hd





43 111/

□□□□□□□□□□43 1---, P B



**76-B4442**

1 P □A. 226)□A36/ 3 PE □  
/12 /0-S 2-E .□m

**76-B4443**

1 P □A. 226)□A36/ 3 PE □  
/12 //-S 3-E .□m

**76-B4444**

1 P □A. 226)□A36/ 3 PE □  
/12 ..-S 3-E .□m

**76-B4462**

3 1 P □A225.  
3 1  
/0-S 2-E .□m

**76-B4463**

3 1 P □A225.  
3 1□  
// -S 3-E .m

**76-B4464**

3 1 P □A225.  
3 1□  
.. -S 3-E .m



**33-T3712/CB**

OM o 00 04. 43 111  
110 113

**76-B4460/1**

3 1 43 □ 113 1

